



U.S. Department
of Transportation

Pipeline and
Hazardous Materials
Safety Administration

East Building, PHH-23
1200 New Jersey Ave, SE
Washington, D.C. 20590

**COMPETENT AUTHORITY CERTIFICATION FOR A
TYPE B(U)
RADIOACTIVE MATERIALS PACKAGE DESIGN
CERTIFICATE USA/9168/B(U)-96, REVISION 4**

The Competent Authority of the United States certifies that the radioactive material package design described in this certificate satisfies the regulatory requirements for a Type B(U) package as prescribed in the regulations of the International Atomic Energy Agency¹ and the United States of America² The package design is approved for use within the United States for import and export shipments made in accordance with applicable international and domestic transport regulations.

1. Package Identification - Model 8-120B.
2. Package Description and Authorized Radioactive Contents - as described in U.S. Nuclear Regulatory Commission Certificate of Compliance No. 9168, Revision 25 (attached).
3. General Conditions -
 - a. Each user of this certificate must have in his possession a copy of this certificate and all documents necessary to properly prepare the package for transportation. The user shall prepare the package for shipment in accordance with the documentation and applicable regulations.
 - b. Each user of this certificate, other than the original petitioner, shall register his identity in writing to the Office of Engineering and Research, (PHH-23), Pipeline and Hazardous Materials Safety Administration, U.S. Department of Transportation, Washington D.C. 20590-0001.

¹ "Regulations for the Safe Transport of Radioactive Material, 2012 Edition, No. SSR-6" published by the International Atomic Energy Agency (IAEA), Vienna, Austria.

² Title 49, Code of Federal Regulations, Parts 100-199, United States of America.

CERTIFICATE USA/9168/B(U)-96, REVISION 4

- c. This certificate does not relieve any consignor or carrier from compliance with any requirement of the Government of any country through or into which the package is to be transported.
 - d. Records of Management System activities required by Paragraph 306 of the IAEA regulations¹ shall be maintained and made available to the authorized officials for at least three years after the last shipment authorized by this certificate. Consignors in the United States exporting shipments under this certificate shall satisfy the applicable requirements of Subpart H of 10 CFR 71.
4. Marking and Labeling - The package shall bear the marking USA/9168/B(U)-96 in addition to other required markings and labeling.
5. Expiration Date - This certificate expires on December 31, 2027. USA/9168/B(U)-96 Revision 3 may be used until December 31, 2022. All other revisions are not authorized for use.

This certificate is issued in accordance with paragraph(s) 810 of the IAEA Regulations and Section 173.471 of Title 49 of the Code of Federal Regulations, in response to the November 18, 2022 petition by EnergySolutions, Columbia, SC, and in consideration of other information on file in this Office.

Certified By:



William Schoonover
Associate Administrator for Hazardous
Materials Safety

December 08, 2022
(DATE)

Revision 4 - Issued to endorse U.S. Nuclear Regulatory Commission Certificate of Compliance No. 9168, Revision 25.

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGE
9168	25	71-9168	USA/9168/B(U)-96	1	OF 4

2. PREAMBLE

- a. This certificate is issued to certify that the package (packaging and contents) described in Item 5 below meets the applicable safety standards set forth in Title 10, Code of Federal Regulations, Part 71, "Packaging and Transportation of Radioactive Material."
- b. This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U.S. Department of Transportation or other applicable regulatory agencies, including the government of any country through or into which the package will be transported.

3. THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION

- a. ISSUED TO (*Name and Address*)
EnergySolutions
740 Osborn Road
Barnwell, SC 29812
- b. TITLE AND IDENTIFICATION OF REPORT OR APPLICATION
Safety Analysis Report for Model 8-120B Type B
Shipping Packaging, Revision No. 14, dated
November 2017.

4. CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10 CFR Part 71, as applicable, and the conditions specified below.

5.

(a) Packaging

- (1) Model No.: 8-120B
- (2) Description

A cylindrical carbon steel, lead shielded, packaging designed for the transport of radioactive waste materials. The packaging has four tie-down and two removable lifting devices and is transported in the upright position with cylindrical foam-filled impact limiters, 102 inches outside diameter (OD), installed at each end of the packaging. The overall height of the package with the impact limiters attached is 132 ¼ inches. The maximum gross weight of the package is approximately 74,000 pounds (lbs), as follows:

Packaging Body	42,220 lbs
Lid	7,080 lbs
Payload	14,150 lbs
Impact Limiters	4,860 lbs (each)
Miscellaneous	830 lbs
Package	74,000 lbs

The cavity of the packaging is a right circular cylinder with an internal diameter of 61 13/16 inches and a height of 74 7/8 inches. The package body consists of two shells, both fabricated of ASTM A516, Grade 70 steel. The annular space between the 1½ inch thick external shell and the ¾ inch thick internal shell is filled with 3.35 inch thick lead. The primary lid is attached to the packaging body with twenty equally spaced 2-inch diameter bolts. A supplemental 14 gauge stainless steel sheet is welded to the inside surface of the primary lid.

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGE
9168	25	71-9168	USA/9168/B(U)-96	2	OF 4

5(a)(2) Packaging Description (Continued)

The centered secondary lid is attached to the primary lid with twelve equally spaced 2-inch diameter bolts. A thermal shield, consisting of two polished stainless-steel plates separated by a thin air gap, is attached to the secondary lid lifting lugs with hitch-pins. A ½ inch thick steel plate covers the central hollow region of the lower impact limiter. A 12 gauge stainless steel liner is welded to the cavity of the package and the lid surface to protect all accessible areas from contamination.

The containment boundary consists of the inner shell, the upper baseplate, the bolting ring, the inner O-rings of the lids, and the lids. Test ports for leak testing of the package are located between the twin O-ring seals for both the primary and secondary lids.

There are three configurations of the packaging: Configuration 1 includes a drain port, sealed with the insertion and welding of a rod in the drain port; Configuration 2 does not have a drain port; Configuration 3 does not have a drain port and the packaging's base plate is fabricated differently than for Configurations 1 and 2. Fabrication of Configurations 1 and 2 is not authorized.

(3) Drawings

The packaging is constructed and assembled in accordance with EnergySolutions Drawing No. C-110-E-0007, 8-120B Shipping Cask, sheets 1-6, Revision No. 24.

The secondary lid thermal shield is constructed in accordance with EnergySolutions Drawing No. DWG-CSK-12CV01-EG-0001-01, 8-120B Cask Secondary Lid Thermal Shield Details, Rev. 4.

(b) Contents

(1) Type and form of material

- (i) Byproduct, source, or special nuclear material in the form of dewatered or grossly dewatered resins, solids, including powdered or dispersible solids, or solidified material, contained within secondary containers; or
- (ii) Radioactive material in the form of activated metals, or metal oxides in solid form, contained within secondary containers.

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

1.	a. CERTIFICATE NUMBER 9168	b. REVISION NUMBER 25	c. DOCKET NUMBER 71-9168	d. PACKAGE IDENTIFICATION NUMBER USA/9168/B(U)-96	PAGE 3	PAGE OF 4
----	-------------------------------	--------------------------	-----------------------------	--	-----------	-----------------

5(b) Contents (Continued)

(2) Maximum quantity of material per package

- (i) Activity not to exceed 3,000 times a Type A quantity along with the following limits:
 - (1) The limit determined per the procedure in Attachment 1 to Chapter No. 7 of the application for beta and gamma emitting radionuclides.
 - (2) The mass limits for fissile materials as prescribed by 10 CFR 71.15 for exempting materials from classification as fissile material.
 - (3) A maximum total package neutron source of 1×10^5 neutrons/second for materials that produce neutrons (other than fissile materials) through any means, including spontaneous fission, alpha-neutron reactions, and gamma-neutron reactions.
- (ii) Maximum decay heat: 200 Watts.
- (iii) Maximum weight of contents: 14,150 lbs including shoring and secondary containers.
- (iv) Powdered or dispersible solid materials must have a mass of at least 60 grams or a specific activity of 50 A_2/g or less.
- (v) Explosives, corrosives, and non-radioactive pyrophorics are prohibited. Pyrophoric radionuclides may be present only in residual amounts below 1 weight percent.
- (vi) Materials that may auto-ignite or change phase at temperatures below 350°F, not including water, shall not be included in the contents. Also, contents shall not include any materials that may cause any significant chemical, galvanic, or any other reaction.
- (vii) Powdered radioactive materials shall not include radioactive forms of combustible metal hydrides or combustible element metals, i.e., magnesium, titanium, sodium, potassium, lithium, zirconium, hafnium, calcium, zinc, plutonium, uranium, and thorium, or combustible non-metals, e.g., phosphorus.
- (viii) Contents may only include quantities of boron, lithium, or beryllium such that these materials do not constitute quantities sufficient to be considered as a bulk material for a payload item or a portion of that payload item.

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGE
9168	25	71-9168	USA/9168/B(U)-96	4 OF	4

6. In addition to the requirements of Subpart G of 10 CFR Part 71:
- (i) The package must be prepared for shipment and operated in accordance with the Operating Procedures of Chapter 7 of the application,
 - (ii) The packaging must be tested and maintained in accordance with the acceptance tests and maintenance program described in Chapter 8 of the application.
7. Except for close fitting contents, shoring must be placed between the secondary containers, or activated components, and the package cavity's walls to prevent both radial and axial movements during transport.
8. Flammable gas (hydrogen) concentration is limited to less than 5% in volume. Compliance with this concentration limit is determined by the methodology used in NUREG/CR-6673.
9. The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR 71.17.
10. Revision No. 24 of this certificate may be used until December 31, 2022.
11. Expiration date: December 31, 2027.

REFERENCES

Safety Analysis Report for Model 8-120B Type B Shipping Packaging, Revision No. 14, November 2017, as supplemented on October 31, 2022.

FOR THE U.S. NUCLEAR REGULATORY COMMISSION



Signed by Diaz-Sanabria, Yaira
on 11/17/22

Yaira Diaz Sanabria, Chief
Storage and Transportation Licensing Branch
Division of Fuel Management
Office of Nuclear Material Safety
and Safeguards

Date: See digital signature



U.S. Department of
Transportation

**Pipeline and
Hazardous Materials
Safety Administration**

East Building, PHH-23
1200 New Jersey Ave, SE
Washington, D.C. 20590

CERTIFICATE NUMBER: USA/9168/B(U)-96

ORIGINAL REGISTRANT(S) :

EnergySolutions
151 Lafayette Drive, Suite 201
Oak Ridge, TN, 37830
USA

EnergySolutions Canada
180 Walker Drive
Brampton, Ontario, L6T4V8
Canada